

# StrapPack®

## Automatic Machine with Stainless Steel Body

The RQ-8xSUS boasts all of the advanced features of the RQ-8x such as strap self-loading, refeed and loop ejection, but adds an attractive and practical stainless steel body.

- The fully enclosed stainless steel cabinet protects the components from water and wash-down spray. The bottom of the cabinet is reinforced to provide extra protection where moisture exposure is greatest. The dispenser can be raised to keep the strap dry.
- The RQ-8xSUS can be built in most of the configurations available in the RQ-8x series. It brings the speed and performance of the RQ-8x into the poultry and meat processing industry.



### ■ Specifications of Standard Arch Size (650 mm wide x 500 mm high or 25" wide x 20" high)

<b>Dimension</b>	<b>Width</b>	1452 mm	57 - 1/8 in.
	<b>Height</b>	1503 mm	59 - 1/8 in.
	<b>Depth</b>	609 mm	24 in.
	<b>Weight</b>	175 kg.	388 lbs.
<b>Package Size</b>	<b>Min.</b>	W 80 X H 30 mm	W 3-1/4 X H 4 in.
	<b>Max. Weight</b>	30 kg	66 lbs.
<b>Joint / Strap/ Coil</b>		heat seal / polypropylene ID 200 X OD 450 X W 200 mm	heat seal / polypropylene ID 8 X OD 18 X W 8 in.
<b>Strap Width</b>		5, 6, 9, 12, (15.5) mm	5mm, 1/4, 3/8, 1/2, (5/8) in.
<b>Strap Tension</b>		Max. 784N (80 kgf)	Max. 178 lbs.
<b>Power Supply</b>		100-120, 200-240 V	1 Phase 50 / 60 Hz 0.65 KVA

# RQ-8xSUS

#### STRAPACK CORPORATION

2-1-19 Hinode Kawasaki-ku, Kawasaki-shi, Kanagawa 210-0824, JAPAN  
Phone 81-(0)44-288-1180 Fax. 81-(0)44-288-1183  
(URL) <http://www.strapack.com> (E-mail) [info@strapack.com](mailto:info@strapack.com)

#### STRAPACK INC.

33508 Central Avenue, Union City, CA 94583-2097 U.S.A.  
Phone 1-510-475-6000 Fax. 1-510-475-6090  
(E-mail) [hayward1@strapack.com](mailto:hayward1@strapack.com)

#### STRAPACK, N.V./S.A.

Uilenbaan 200, B-2160 Wommelgem, BELGIUM  
Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521  
(E-mail) [europe@strapack.be](mailto:europe@strapack.be)